

background noise involved in a signal, so that process of signal processing by the FFT method can be advanced.

References

- Bosselmann, t., reule, a., schroeder, j., 1984. fiber-optic temperature sensor using fluorescence decay time. *SPIE*. **514**,151-154.
- Castrellon, j., Paez, G., Strojnik, M., 2002. Remote temperature sensor employing erbium-doped silica fiber. *Infrared physics and Technology* **43**, 219-222.
- Castrellon-Uribe, J., Paez, G., Strojnik, M., 2002. Radiometric analysis of a fiber optic temperature sensor. *SPIE*. **4486**, 164-169.
- Grattan, K.T.V., Palmer, A.W., Hang, Z.Z., 1991. Development of a high-temperature fiber-optics thermometer probe using fluorescent decay. *Rev. sci. Instrum.* **62(5)**, 1210-1213.
- Paez, G., Strojnik, M., 2003. erbium-doped optical fiber fluorescence temperature sensor with enhanced sensitivity, a high signal-to-noise ratio, and a power ratio in the 520-530- and 55-560-nm bands. *Applied Optics* **42(16)**, 3251-3258.
- Paez, g., strojnik, m., 2003. experimental results of ratio-based erbium-doped-silica temperature sensor. *Optical Engineering* **42(6)**, 1805-1811.
- Reule, A., Schroeder, J., 1986. Fluorescence decay temperature sensor with optimized signal processing. *SPIE*. **658**, 52-58.
- Sholes, R.R., Small, J.G., 1980. fluorescent decay thermometer with biological applications. *Rev. Sci. Instrum.* **51(7)**, 882-884.
- Sidiropiou, F., Wade, S.A., dragomir, N.M., 2003. effects of high-temperature heat treatment on Nd³⁺-doped optical fibers for use in fluorescence intensity ratio based temperature sensing. *Review of Scientific Instruments* **4(7)**, 3524-3530.
- Sun, T., Grattan, K.T.V., Sun, W.M., 2002. fluorescence based on optical fiber fire alarm system. proceeding OFS2002. hilton portland, USA, 471-474.
- Sun, W.M., zhang, J.Z., yu, L., 2004. measurement of decay time based on FFT. *Optics and Laser Technology* **36(4)**, 323-326.
- Vergara, M.C., Wade, S.W., He, Y.P., 1999. the application of an optical fiber temperature sensor in the investigation of window glass breakage in fires. *INTERFLAM*. **99**, 1417-1422.
- Wade, S.A., Collin, S.F., baxter, G.W., 2001. effect of strain on temperature measurements using the fluorescence intensity ratio technique (with Nd³⁺-and Yb³⁺-doped silica fibers). *Review of Scientific Instruments* **72(8)**, 3180-3185.
- Wade, S.A., Collins, S.F., Baxter, G.W., 2003. fluorescence intensity ratio technique for optical fiber point temperature sensing. *Journal of Applied Physics* **94(8)**, 4743-4756.
- Wade, S.A., Muscat, J.C., Collins, S.F., 1999. Nd³⁺-doped optical fiber temperature sensor using the fluorescence intensity ratio technique. *Review of Scientific Instruments* **70(11)**, 4279-4282.
- Wang, X.F., Uchida, T., Coleman, D.M., 1991. a two-dimensional fluorescence lifetime imaging system using a gated image intensifier. *Appl. Spectrosc* **45(3)**, 360-366.
- Zhang, Z.Y., Grattan, K.T.V., Hu, Y.L., 1996. prony's method for exponential lifetime estimations in fluorescence-based thermometers. *Review of Scientific Instruments* **67(7)**, 2590-2594.
- Zhang, Z.Y., Grattan, K.T.V., Palmer, A.W., 1991. A novel signal processing scheme for a fluorescence based fiber-optic temperature sensor. *Rev. Sci. Instrum.* **62(7)**, 1735-1742.
- Zhang, Z.Y., Grattan, K.T.V., palmer, A.W., 1993. temperature dependence of fluorescence lifetimes in -doped insulating crystal. *phys. rev. B* **48(11)**, 7772-7778.